



DM-SP THIN WALL TUBING

Skid proof heat shrink tubing

Application

Polyolefin material, excellent application for various fishing tackles, sport fittings, any equipments and commodities with hand device.

Features

Operating Temperature: -55°C ~ 105°C

Shrink Temperature: Started at 70°C, full recovery at 110°C

RoHS Compliant

Good flexibility, abrasion resistant and anti-skid performance

Standard Color: Black, Red, Yellow, White, Green, Blue

Shrink Ratio: 1.8:1



Technical Data

Property	Property	Property
Tensile Strength (Mpa)	ASTM D412	10.4 Mpa
Longitudinal Elongation (%)	ASTM D412	≤8
Elongation (%)	ISO 1210	200%

Dimensions

Size	As Supplied (mm)		After Recovery (mm)		Standard length m/pcs
	DM-SP mm. (D)	Inside Diameter Min. (D)	Wall Thickness Nominal. (T)	Inside Diameter Max. (d)	
15	≥15	0.45±0.15	8	0.85±0.15	1.0
20	≥20	0.50±0.15	11	0.90±0.15	0.8/1.0/1.6
22	≥22	0.50±0.15	12.5	0.90±0.15	0.8/1.0/1.6
25	≥25	0.50±0.15	14.5	1.00±0.15	0.8/1.0/1.6
28	≥28	0.50±0.15	15.5	1.00±0.15	0.8/1.0/1.6
30	≥30	0.60±0.15	17.5	1.20±0.15	0.8/1.0/1.6
35	≥35	0.60±0.15	20	1.20±0.15	0.8/1.0/1.6
40	≥40	0.60±0.15	23	1.20±0.15	0.8/1.0/1.6
45	≥45	0.65±0.15	25	1.25±0.15	0.8/1.0/1.6
50	≥50	0.65±0.15	28	1.25±0.15	0.8/1.0/1.6



*Spools as standards. 1 m. or 1,22 m. sticks, special spool lengths or cut pieces available on request.