



## DC-BS

### MECHANICAL & THERMAL PROTECTION

Expandable polyester braided sleeving

#### Applications

The expandable sleeving offers an excellent protection in many industrial applications and also can provide an agreeable personalization and identification of the brand.

#### Features

Material of Polyester braided sleeve. It offers a continuous working temperature of - 50°C to +150°C, which have a good resistance to abrasion and a high expansion rate.

#### Various

It's possible to realize a wide range of patterns and colors upon request.

#### Technical Data

Test Method	Values
Material	Polyester
Operating range	50°C±150°C
Melt point	240±10°C
Flammability	VW-1

#### Dimensions

Inside diameter		Expanded range mm		Standard package m/roll
Nominal size (inch)	Nominal size (mm)	Min inner Dia	Max outer Dia	
1/8"	3	1	6	1000 m
1/4"	6	3	9	500 m
5/16"	8	5	16	350 m
3/8"	10	7	19	350 m
1/2"	12	8	24	300 m
5/8"	16	10	27	250 m
3/4"	19	14	30	200 m
1"	25	18	35	200 m
1 1/4"	30	20	50	150 m
1 1/2"	40	30	60	100 m
1 3/4"	45	35	75	100 m
2"	50	40	80	100 m
2 1/2"	64	45	105	100 m
3"	76	64	120	100 m

\*special spool lengths or cut pieces available on request.