



## DM-CF MECHANICAL & THERMAL PROTECTION

### Corrugated Flexible Conduit Sleeve

#### Applications

Corrugated flexible wire sleeve offers you wide range technical properties for your cable and wire management applications against not only mechanical damage but also the influences of UV radiation, weathering and chemicals. The flexible body allows for the cables in the corner and elbow. We also supply the split style for easy installation and removal.

#### Features

Highly abrasion resistance, resist acids, solvents and fuels resistant.

#### Material :

1:PE

2:PA

3:PP

Operating range:

1 : - 40°C -- +90°C

2 : -40°C -- +130°C

3 -30°C -- +110°C

Standard colour : black /gray.

**Type** :open or closed

**Certificate**: RoHS

#### Dimensions

PE/PA/PP OD (mm)	ID*OD (mm)	Bending radius (R±10%)	Packing (m/roll)
Φ7	4.5*7.0	5.0	200m/roll
Φ8.5	5.5*8.5	8.0	100m/roll
Φ10	7.0*10.0	10.0	100m/roll
Φ12	8.5*11.5	15.0	100m/roll
Φ13	10*13	20.0	100m/roll
Φ15.8	12*15.8	30.0	100m/roll
Φ18.5	14.3*18.5	40.0	100m/roll
Φ21.2	17*21.2	45.0	100m/roll
Φ25	21*25	50.0	100m/roll
Φ28.5	23*28.5	55.0	50m/roll
Φ34.5	29*34.5	60.0	50m/roll
Φ42.5	36*42.5	70.0	25m/roll
Φ54.5	48*54.5	80.0	25m/roll

Available in spool, coils or cut pieces (on request).