




DM-CRB

OTHER PRODUCTS

Cold Shrink Silicone Rubber Breakout

Features

- Simple and fast installation meeting a variety of configuration requirements.
- Providing sealing protection over multi-core cable crutch, including 3-,4-,5-,6-core breakouts.



Dimensions

Cores	ØC Expanded (max)/mm	Application Range/mm	ØF Expanded (max)/mm	Application Range/mm	L _F /mm	L _C /mm
2	47	Φ23-Φ37	20	Φ8-Φ15	35	100
2	65	Φ30-Φ55	25	Φ10-Φ20	35	110
2	80	Φ34-Φ57	32	Φ15-Φ25	35	120
2	110	Φ44-Φ95	47	Φ20-Φ40	35	130
3	56	Φ30-Φ43	20	Φ10-Φ15	35	105
3	65	Φ36-Φ55	25	Φ13-Φ20	35	125
3	80	Φ46-Φ67	32	Φ19-Φ26	45	130
3	88	Φ54-Φ78	35	Φ21-Φ31	45	135
3	104	Φ62-Φ90	40	Φ25-Φ33	45	150
3	120	Φ72-Φ105	47	Φ31-Φ40	45	165
3	140	Φ88-Φ120	60	Φ36-Φ52	55	180
3	150	Φ88-Φ128	65	Φ36-Φ57	55	180
3	165	Φ88-Φ138	70	Φ36-Φ62	55	180
4	60	Φ26-Φ45	20	Φ10-Φ14	35	126
4	70	Φ36-Φ55	25	Φ12-Φ17	40	137
4	88	Φ51-Φ75	32	Φ14-Φ25	40	145
4	120	Φ56-Φ92	47	Φ19-Φ40	40	160
5	80	Φ36-Φ62	20	Φ10-Φ14	40	123
5	88	Φ46-Φ73	25	Φ12-Φ17	40	134
5	110	Φ59-Φ95	35	Φ16-Φ27	45	138
5	120	Φ59-Φ100	40	Φ16-Φ32	45	138
6	104	Φ44-Φ80	32	Φ14-Φ25	60	135
6	80	Φ36-Φ62	14 25	Φ6-Φ8 Φ10-Φ20	45	130
6	104	Φ44-Φ80	28 35	Φ14-Φ21 Φ14-Φ24	45	135
6	104	Φ48-Φ90	30 32	Φ10-Φ15 Φ15-Φ25	45	135
6	120	Φ60-Φ100	25 40	Φ10-Φ20 Φ21-Φ30	45	135
6	140	Φ75-Φ120	28 47	Φ15-Φ22 Φ26-Φ40	45	145

Notes: 1. 6-Core breakouts (with 3 big fingers and 3 small fingers) are used on trailing cable, variable frequency cables, telecommunication cables, control cables, etc.

2. Special specification is available per different requirements.