



DM-CS (EPDM) OTHER PRODUCTS

Cold Shrink EPDM Tubing

Features

- Manufactured from EPDM rubber.
- Accommodating a wide range of cable sizes.
- For indoor or outdoor applications.
- Offering good mechanical, insulation and sealing protection.
- Simple and fast installation.

Technical data

Item	Unit	Standard Value	Typical Value	Standard
Nominal color	-	Black	-	-
Hardness	Shore A	40±5	38	GB/T531
Tensile strength	MPa	≥ 6.0	8	GB/T528
Elongation at break	%	≥ 600	700	GB/T528
Tear strength	KN/m	≥ 20	22	GB/T529
Electrical strength	KV/mm	≥ 14	15	GB/T 1408

Dimensions

Spec	Size	Application Range (mm)	Length after Relaxed (mm)	Color
DM-CS(E)-20	Φ20	8~15	50~550	Black
DM-CS(E)-25	Φ25	10~20	50~550	Black
DM-CS(E)-35	Φ35	14~30	50~550	Black
DM-CS(E)-40	Φ40	17.5~33	50~550	Black
DM-CS(E)-53	Φ53	25~46	50~550	Black
DM-CS(E)-70	Φ70	32~63	50~470	Black
DM-CS(E)-104	Φ104	43~94	50~470	Black
DM-CS(E)-125	Φ125	46~114	50~470	Black
DM-CS(E)-150	Φ150	55~135	50~470	Black

*The inner diameter, thickness and length can be customised