



DM-PVCIWG OTHER PRODUCTS

Imitation wood grain PVC heat shrinkable tube

Product introduction:

Imitation wood grain heat shrinkable casing is environmentally friendly PVC heat shrinkable casing as medium, through special pro-cessing, the surface covering wood grain formed vivid natural imita-tion wood grain effect Scope of application Product

Specifications:

φ10-φ40, widely used in curtain rod, shower curtain rod, poles, furniture hang lever need wood grain effects, such as plastic pipe to outsourcing. Lateral contraction ratio: 2:1

Product categories:

Ordinary light type common matte type increase light enhance matte. The difference between: Matte type products: look from the look and feel, than the softer, more close to natural light type products .Enhanced products: add the anti-uv. agents, cold resistance, anti-aging products, cold resistance, resistance performance than ordinary products greatly increased.



Dimensions

No.	Size	Fold diameter (mm)	Single layer thickness (mm)	Applicable outside diameter of pipe (mm)	Long conversion
					1000 m ≈ kg
1	φ10	16.8+0.5	0.10±0.02	Φ7.5-φ8.7	4.8
2	φ11	18.1+1.0		Φ8.8-φ9.7	5.2
3	Φ12	20.0+1.0		Φ9.8-φ10.7	5.8
4	Φ13	21.5+1.0		Φ10.8-φ11.7	6.2
5	Φ14	23.5+1.0		Φ11.8-φ12.7	6.8
6	Φ15	24.5+1.0		Φ12.8-φ13.7	7.1
7	Φ16	27.0+0.5		Φ13.8-φ14.7	7.5
8	Φ17	28.0+1.0		Φ14.8-φ15.5	7.9
9	Φ18	29.0+1.0		Φ15.6-φ16.5	8.2
10	Φ19	31.0+0.6		Φ16.6-φ17.5	8.7
11	Φ20	32.5+1.0	0.12±0.02	Φ17.6-φ18.5	11.1
12	Φ21	34.0+1.0		Φ18.6-φ19.5	11.6
13	Φ22	35.5+1.0		Φ19.6-φ20.0	12.2
14	Φ23	36.5+1.0		Φ20.6-φ21.0	12.8
15	Φ24	39.0+1.0		Φ21.6-φ22.0	13.2
16	Φ25	41.0+1.5		Φ22.6-φ23.0	14.4
17	Φ26	43.5+1.5		Φ23.1-φ24.0	14.8
18	Φ27	45.0+1.5		Φ24.1-φ25.0	15.2
19	Φ28	46.5+1.5		Φ25.1-φ26.0	15.8
20	Φ29	48.5+1.5		Φ26.1-φ27.0	20.7
21	Φ30	50.0+1.5	0.15±0.25	Φ27.1-φ27.5	21.3
22	Φ33	52.0+1.5		Φ27.6-φ30.5	22.2
23	Φ34	56.5+1.5		Φ30.6-φ31.5	24.2
24	Φ35	58.0+1.5		Φ31.6-φ32.5	24.6
25	Φ36	59.5+1.5		Φ32.6-φ33.5	25.4
26	Φ38	63.5+1.5		Φ33.6-φ35.0	27.1
27	φ40	65.0+2.0		Φ35.1-φ37.0	27.7